



intelligent load feeder reversing starter standard 3.5-32 A up to 690 V AC type of coordination 2 frame size S0 for ET 200SP system consisting of 3RC7141-4EE01, 3RV2321-4EC20, 2x 3RT2027-2BB40

product brand name	SIRIUS
product designation	Intelligent load feeder
design of the product	reversing starter standard
product type designation	3RA8
manufacturer's article number	
• of the supplied contactor	<a href="#">3RT2027-2BB40</a>
• of the supplied circuit-breakers	<a href="#">3RV2321-4EC20</a>
• of the supplied RH assembly kit	<a href="#">3RA2923-2LB2</a>
• of the supplied link module	<a href="#">3RC7141-4EE01</a>
• of the supplied DIN-rail adapter	<a href="#">3RA2922-1AA00</a>
<b>General technical data</b>	
number of monitored phases	2
suitability for use	
• direct starter	No
• reversing starter	Yes
• star-delta starter	No
product function external reset	Yes
product component RESET button	Yes
design of the overcurrent release	electronic
size of the circuit-breaker	S0
size of load feeder	S0
size of contactor can be combined company-specific	S0
product function	
• remote firmware update	Yes
• disconnector functionality	Yes
• for power supply reverse polarity protection	Yes
power loss [W] for rated value of the current at AC in hot operating state per pole	6.7 W
insulation voltage	
• rated value	690 V
• for overvoltage category III according to IEC 60664 with degree of pollution 2 rated value	690 V
degree of pollution	3
overvoltage category	3
surge voltage resistance rated value	6 kV
protection class IP	
• on the front	IP20
• of the terminal	IP20
shock resistance according to IEC 60068-2-27	6g / 11,0 ms (3 shocks); 10g / 6,0 ms (1000 shocks)
vibration resistance	5-8,4 Hz, 3,5 mm; 8,4-150 Hz, 1 g; 10 cycles / 10-60 Hz, 0,35 mm; 60-500 Hz

	5 g; 10 cycles
<b>type of coordination</b>	2
<b>reference code according to IEC 81346-2</b>	Q
<b>reference code according to IEC 81346-2:2019</b>	Q
<b>continuous current rated value</b>	32 A
<b>Substance Prohibitance (Date)</b>	06/21/2024
<b>SVHC substance name</b>	Lead - 7439-92-1 Lead monoxide (lead oxide) - 1317-36-8 Silicic acid, lead salt - 11120-22-2 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol - 79-94-7 Lead titanium zirconium oxide - 12626-81-2
<b>Net Weight</b>	2.589 kg
<b>Ambient conditions</b>	
installation altitude at height above sea level maximum	2 000 m
<b>ambient temperature</b>	
• during operation	-20 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
• with upper limit without restrictions	40 °C
environmental category during operation according to IEC 60721	3C3 (without salt spray)
relative humidity during operation	10 ... 95 %
<b>Main circuit</b>	
<b>number of poles for main current circuit</b>	3
<b>design of the switching contact</b>	electromechanical
<b>adjustable current response value current of the current-dependent overload release</b>	3.5 ... 32 A
<b>type of the motor protection</b>	solid-state
<b>type of voltage for main current circuit</b>	AC
<b>utilization category according to IEC 60947-4-1</b>	AC-3e
<b>operating voltage</b>	
• rated value	690 V
• at AC-3 rated value maximum	690 V
• at AC-3e rated value maximum	690 V
<b>operating frequency rated value</b>	50 ... 60 Hz
<b>operational current rated value</b>	32 A
<b>operational current</b>	
• at AC-3	
— at 400 V rated value	32 A
— at 440 V rated value	32 A
— at 500 V rated value	32 A
— at 690 V rated value	21 A
• at AC-3e	
— at 400 V rated value	32 A
— at 440 V rated value	32 A
— at 500 V rated value	32 A
— at 690 V rated value	21 A
<b>operating power</b>	
• at AC-3	
— at 400 V rated value	15 000 W
— at 500 V rated value	15 000 W
— at 690 V rated value	18 500 W
• at AC-3e	
— at 400 V rated value	15 000 W
— at 500 V rated value	15 000 W
— at 690 V rated value	18 500 W
<b>Control circuit/ Control</b>	
<b>type of voltage of the control supply voltage</b>	DC
closing delay at DC	50 ... 170 ms
opening delay at DC	30 ... 50 ms

Auxiliary circuit	
product component auxiliary switch	No
product extension auxiliary switch	Yes
type of voltage for auxiliary and control circuit	DC
auxiliary voltage at DC rated value	24 V
auxiliary voltage at DC rated value	20.4 ... 28.8 V
inrush current peak for auxiliary voltage at DC at 24 V	2.5 A
duration of inrush current peak for auxiliary voltage at DC at 24 V	1 ms
power loss [W] at the auxiliary voltage in holding operation at DC at 24 V	1.3 W
Protective and monitoring functions	
type of protection function of the overcurrent release	electronic
product function	
• ground fault detection	No
• phase failure detection	Yes
• phase sequence recognition	Yes
• overcurrent detection 1 phase	Yes
• underright current detection 3 phases	Yes
• underright current monitoring	Yes
• overcurrent and underright current monitoring	Yes
• underright current detection 1 phase	Yes
• overcurrent detection 3 phase	Yes
• overload protection	Yes
• overload warning	Yes
• temperature-compensated overload protection	No
• motor protection	Yes
• active current monitoring	No
• main switches with supply disconnect function and EM-STOP switches	No
• operating hours counter	Yes
trip class	CLASS 10E / CLASS 20E
design of the overload release	electronic
response value current of instantaneous short-circuit trip unit	400 A
UL/CSA ratings	
conditional short-circuit current (I <sub>q</sub> ) with type of coordination 1	
• at 480 AC Y/277 V rated value	50 000 A
• at AC 600 Y/347 V rated value	30 000 A
operating voltage	
• according to UL 60947 rated value	480 V
• at AC at 60 Hz according to CSA and UL rated value	480 V
Short-circuit protection	
product function short circuit protection	Yes
design of the short-circuit trip	magnetic
conditional short-circuit current (I <sub>q</sub> )	
• at 690 V according to IEC 60947-4-1 rated value	1 000 A
• at 400 V according to IEC 60947-4-1 rated value	150 000 A
• at 440 V according to IEC 60947-4-1 rated value	100 000 A
• at 500 V according to IEC 60947-4-1 rated value	70 000 A
conditional short-circuit current (I <sub>q</sub> ) with type of coordination 2	
• at 230 V rated value	150 000 A
• at 400 V rated value	150 000 A
certificate of suitability ATEX	No
Installation/ mounting/ dimensions	
mounting position	vertical, on horizontal standard mounting rail
fastening method	screw and snap-on mounting onto 35 mm DIN rail
• mounting rail	Yes
height	269 mm

<b>width</b>	90 mm
<b>depth</b>	174 mm
<b>required spacing</b>	
• for grounded parts at 400 V	
— downwards	10 mm
— upwards	30 mm
— backwards	0 mm
— at the side	9 mm
— forwards	0 mm
• for live parts at 400 V	
— downwards	10 mm
— upwards	30 mm
— backwards	0 mm
— at the side	9 mm
— forwards	0 mm
• for grounded parts at 500 V	
— downwards	10 mm
— upwards	30 mm
— backwards	0 mm
— at the side	20 mm
— forwards	0 mm
• for live parts at 500 V	
— downwards	10 mm
— upwards	30 mm
— backwards	0 mm
— at the side	20 mm
— forwards	0 mm
• for grounded parts at 690 V	
— downwards	10 mm
— upwards	80 mm
— at the side	20 mm
— forwards	0 mm
• for live parts at 690 V	
— downwards	10 mm
— upwards	80 mm
— at the side	20 mm
— forwards	0 mm

<b>Connections/ Terminals</b>	
<b>product component removable terminal for auxiliary and control circuit</b>	No
<b>type of electrical connection</b>	
• for main current circuit	spring-loaded terminals
• for auxiliary and control circuit	spring-loaded terminals (push-in)
<b>type of electrical connection for supply voltage line-side</b>	spring-loaded terminals (push-in)
<b>type of connectable conductor cross-sections</b>	
• for main contacts	
— solid	2x (1 ... 10 mm <sup>2</sup> )
— stranded	2x (1 ... 10 mm <sup>2</sup> )
— finely stranded with core end processing	2x (1 ... 6 mm <sup>2</sup> )
• for AWG cables for main contacts	2x 18 ... 8
<b>connectable conductor cross-section for main contacts</b>	
• solid	1 ... 10 mm <sup>2</sup>
• stranded	1 ... 10 mm <sup>2</sup>
• finely stranded with core end processing	1 ... 6 mm <sup>2</sup>
<b>type of connectable conductor cross-sections at the inputs for supply voltage</b>	
• solid	0.2 ... 1.5 mm <sup>2</sup>
• finely stranded without core end processing	0.2 ... 1.5 mm <sup>2</sup>
• finely stranded with core end processing	0.2 ... 1.0 mm <sup>2</sup>

type of connectable conductor cross-sections at the inputs for supply voltage for AWG cables solid	24 ... 16		
<b>Electrical Safety</b>			
<b>touch protection against electrical shock</b>	IP20		
<b>touch protection on the front according to IEC 60529</b>	finger-safe		
<b>Communication/ Protocol</b>			
protocol is supported other protocols	Yes		
<b>product function bus communication</b>	Yes		
product function control circuit interface with IO link	No		
product function control circuit interface with AS-interface	No		
<b>data volume</b>			
• of the address range of the inputs with cyclical transfer total	16 byte		
• of the address range of the outputs with cyclical transfer total	2 byte		
<b>address space memory of address range</b>			
• of the inputs	16 byte		
• of the outputs	2 byte		
type of electrical connection of the communication interface	RJ45		
<b>Electromagnetic compatibility</b>			
<b>conducted interference</b>			
• due to burst according to IEC 61000-4-4	2 kV		
• due to conductor-earth surge according to IEC 61000-4-5	2 kV		
• due to conductor-conductor surge according to IEC 61000-4-5	1 kV		
• due to high-frequency radiation according to IEC 61000-4-6	10 V		
<b>field-based interference according to IEC 61000-4-3</b>	10 V/m		
<b>electrostatic discharge according to IEC 61000-4-2</b>	8 kV air discharge		
<b>conducted HF interference emissions according to CISPR11</b>	Class A for industrial environment		
<b>field-bound HF interference emission according to CISPR11</b>	Class A for industrial environment		
<b>Supply voltage</b>			
<b>type of voltage of the supply voltage</b>	DC		
<b>supply voltage 1 at DC rated value</b>			
• minimum permissible	19.2 V		
• maximum permissible	28.8 V		
<b>auxiliary voltage at DC rated value</b>	20.4 ... 28.8 V		
<b>supply voltage at DC rated value</b>	24 V		
<b>inrush current peak with supply voltage at DC at 24 V</b>	1.25 A		
<b>duration of inrush current peak with supply voltage at DC at 24 V</b>	5 ms		
<b>power loss [W] at supply voltage at DC at 24 V</b>	0.5 W		
<b>Approvals Certificates</b>			
<b>General Product Approval</b>	<b>EMV</b>	<b>Test Certificates</b>	<b>other</b>



EG-Konf.



[Type Test Certificates/Test Report](#)

[Confirmation](#)

other

Environment



[Environmental Confirmations](#)

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA8522-4EE00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RA8522-4EE00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA8522-4EE00&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA8522-4EE00&lang=en)

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA8522-4EE00>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



