



SIPLUS ET 200SP AI 4xI 2-/4-wire standard based on 6ES7134-6GD01-0BA1 with conformal coating, -40...+70 °C, analog input module, suitable for BU type A0, A1, color code CC03, module diagnostics, 16-bit, +/-0.3%

| General information  |   |
|--|---|
| Product type designation   | AI 4xI 2-/4-wire ST   |
| based on   | <a href="#">6ES7134-6GD01-0BA1</a>                                |
| usable BaseUnits   | BU type A0, A1  |
| Color code for module-specific color identification plate  | CC03  |
| Product function   |   |
| <ul style="list-style-type: none"> <li>• I&amp;M data</li> <li>• Isochronous mode</li> <li>• Measuring range scalable</li> </ul> | Yes; I&M0 to I&M3<br>No<br>No                                     |
| Engineering with   |   |
| <ul style="list-style-type: none"> <li>• STEP 7 TIA Portal configurable/integrated from version</li> </ul>                       | see entry ID: 109746275   |
| Operating mode   |   |
| <ul style="list-style-type: none"> <li>• Oversampling</li> <li>• MSI</li> </ul>  | No<br>No  |
| CiR - Configuration in RUN   |   |
| Reparameterization possible in RUN   | Yes   |
| Calibration possible in RUN  | No  |
| Supply voltage   |   |
| Rated value (DC)   | 24 V  |
| permissible range, lower limit (DC)  | 19.2 V  |
| permissible range, upper limit (DC)  | 28.8 V  |
| Reverse polarity protection  | Yes   |
| Input current  |   |
| Current consumption, max.  | 37 mA; without sensor supply                                      |
| Encoder supply   |   |
| 24 V encoder supply  |   |
| <ul style="list-style-type: none"> <li>• 24 V</li> <li>• Short-circuit protection</li> <li>• Output current, max.</li> </ul>     | Yes<br>Yes<br>20 mA; max. 50 mA per channel for a duration < 10 s |
| Power loss   |   |
| Power loss, typ.   | 0.85 W; Without encoder supply voltage                            |
| Address area   |   |
| Address space per module   |   |
| <ul style="list-style-type: none"> <li>• Address space per module, max.</li> </ul>   | 8 byte; + 1 byte for QI information                               |
| Hardware configuration   |   |
| Automatic encoding   | Yes   |
| <ul style="list-style-type: none"> <li>• Mechanical coding element</li> <li>• Type of mechanical coding element</li> </ul>       | Yes<br>Type A   |
| Selection of BaseUnit for connection variants  |   |

|  |  |
|--|--|
| • 2-wire connection  | BU type A0, A1   |
| • 4-wire connection  | BU type A0, A1   |
| <b>Analog inputs</b>   |  |
| Number of analog inputs  | 4; > 60 °C max. 1x ±20 mA permissible  |
| permissible input current for current input (destruction limit), max.                      | 50 mA  |
| Cycle time (all channels), min.  | Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels) |
| <b>Input ranges (rated values), currents</b>   |  |
| • 0 to 20 mA<br>— Input resistance (0 to 20 mA)  | Yes; 16 bit incl. sign<br>100 Ω; + approx. 0.7 V diode forward voltage in 2-wire operation                                   |
| • -20 mA to +20 mA<br>— Input resistance (-20 mA to +20 mA)                                | Yes<br>100 Ω   |
| • 4 mA to 20 mA<br>— Input resistance (4 mA to 20 mA)                                      | Yes; 15 bit<br>100 Ω; + approx. 0.7 V diode forward voltage in 2-wire operation  |
| <b>Cable length</b>  |  |
| • shielded, max.   | 1 000 m  |
| <b>Analog value generation for the inputs</b>  |  |
| Measurement principle  | integrating (Sigma-Delta)  |
| Integration and conversion time/resolution per channel                                     |  |
| • Resolution with overrange (bit including sign), max.                                     | 16 bit   |
| • Integration time, parameterizable  | Yes  |
| • Interference voltage suppression for interference frequency f1 in Hz                     | 16.6 / 50 / 60 Hz  |
| • Conversion time (per channel)  | 180 / 60 / 50 ms   |
| <b>Smoothing of measured values</b>  |  |
| • Number of smoothing levels   | 4; None; 4/8/16 times  |
| • parameterizable  | Yes  |
| <b>Encoder</b>   |  |
| Connection of signal encoders  |  |
| • for voltage measurement  | No   |
| • for current measurement as 2-wire transducer   | Yes  |
| — Burden of 2-wire transmitter, max.   | 650 Ω  |
| • for current measurement as 4-wire transducer   | Yes  |
| <b>Errors/accuracies</b>   |  |
| Linearity error (relative to input range), (+/-)   | 0.01 %   |
| Temperature error (relative to input range), (+/-)   | 0.005 %/K  |
| Crosstalk between the inputs, min.   | 50 dB; Applies to up to ±5 V overvoltage in other channels   |
| Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)                  | 0.05 %   |
| Operational error limit in overall temperature range                                       |  |
| • Current, relative to input range, (+/-)  | 1 %  |
| Basic error limit (operational limit at 25 °C)   |  |
| • Current, relative to input range, (+/-)  | 0.3 %  |
| Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency     |  |
| • Series mode interference (peak value of interference < rated value of input range), min. | 70 dB  |
| • Common mode voltage, max.  | 10 V   |
| • Common mode interference, min.   | 90 dB  |
| <b>Interrupts/diagnostics/status information</b>   |  |
| Diagnostics function   | Yes  |
| <b>Alarms</b>  |  |
| • Diagnostic alarm   | Yes  |
| • Limit value alarm  | No   |
| <b>Diagnoses</b>   |  |
| • Monitoring the supply voltage  | Yes  |
| • Wire-break   | Yes; at 4 to 20 mA   |
| • Short-circuit  | Yes; 2-wire mode: Short-circuit of the encoder supply to ground or of an input to the encoder supply                         |
| • Group error  | Yes  |

|   |  |
|---|--|
| • Overflow/underflow  | Yes  |
| Diagnostics indication LED  |  |
| • Monitoring of the supply voltage (PWR-LED)  | Yes; green LED   |
| • Channel status display  | Yes; green LED   |
| • for channel diagnostics   | No   |
| • for module diagnostics  | Yes; green/red LED   |
| Potential separation  |  |
| Potential separation channels   |  |
| • between the channels  | Yes; channel group-specific between 2-wire current input group and 4-wire voltage input group  |
| • between the channels and backplane bus  | Yes  |
| • between the channels and the power supply of the electronics  | Yes; only for 4-wire transducer  |
| Permissible potential difference  |  |
| between the inputs (UCM)  | 10 V DC  |
| Isolation   |  |
| Isolation tested with   | 707 V DC (type test)   |
| Ambient conditions  |  |
| Ambient temperature during operation  |  |
| • horizontal installation, min.   | -40 °C; = Tmin (incl. condensation/frost)  |
| • horizontal installation, max.   | 70 °C; = Tmax; > 60 °C max. 1x ±20 mA permissible  |
| • vertical installation, min.   | -40 °C; = Tmin   |
| • vertical installation, max.   | 50 °C; = Tmax  |
| Altitude during operation relating to sea level   |  |
| • Installation altitude above sea level, max.   | 5 000 m  |
| • Ambient air temperature-barometric pressure-altitude  | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity   |  |
| • With condensation, tested in accordance with IEC 60068-2-38, max.   | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation  |
| Resistance  |  |
| Coolants and lubricants   |  |
| — Resistant to commercially available coolants and lubricants   | Yes; Incl. diesel and oil droplets in the air  |
| Use in stationary industrial systems  |  |
| — to biologically active substances according to EN 60721-3-3   | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request   |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *   |
| — to mechanically active substances according to EN 60721-3-3   | Yes; Class 3S4 incl. sand, dust, *   |
| — Against mechanical environmental conditions acc. to EN 60721-3-3  | Yes; Class 3M8 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)   |
| Use on ships/at sea   |  |
| — to biologically active substances according to EN 60721-3-6   | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request  |
| — to chemically active substances according to EN 60721-3-6   | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *   |
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *   |
| — Against mechanical environmental conditions acc. to EN 60721-3-6  | Yes; Class 6M4 using the SIPLUS Mounting Kit ET 200SP (6AG1193-6AA00-0AA0)   |
| Usage in industrial process technology  |  |
| — Against chemically active substances acc. to EN 60654-4   | Yes; Class 3 (excluding trichlorethylene)  |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)                              |
| Remark  |  |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation!   |
| Conformal coating   |  |

- Coatings for printed circuit board assemblies acc. to EN 61086
- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Class 2 for high reliability

Yes; Type 1 protection

Yes; Discoloration of coating possible during service life

Yes; Conformal coating, Class A

#### Dimensions

|        |       |
|--------|-------|
| Width  | 15 mm |
| Height | 73 mm |
| Depth  | 58 mm |

#### Weights

|                 |      |
|-----------------|------|
| Weight, approx. | 31 g |
|-----------------|------|

#### Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-26-01    |
| eClass | 12      | 27-24-26-01    |
| eClass | 9.1     | 27-24-26-01    |
| eClass | 9       | 27-24-26-01    |
| eClass | 8       | 27-24-26-01    |
| eClass | 7.1     | 27-24-26-01    |
| eClass | 6       | 27-24-26-01    |
| ETIM   | 10      | EC001596       |
| ETIM   | 9       | EC001596       |
| ETIM   | 8       | EC001596       |
| ETIM   | 7       | EC001596       |
| IDEA   | 4       | 3562           |
| UNSPSC | 15      | 32-15-17-05    |

#### Approvals / Certificates

##### General Product Approval

##### EMV

##### [Manufacturer Declaration](#)



##### [China RoHS](#)



##### For use in hazardous locations



IECEx



##### [CCC-Ex](#)



##### Maritime application

last modified: 10/23/2025