

## Data sheet

## 6AG1223-1PH32-2XB0



Figure similar

SIPLUS S7-1200 SM 1223 8DI/8DQ/relay based on 6ES7223-1PH32-0XB0 with conformal coating, -40...+70 °C, start up -25 °C, digital input/output 8 DI/8 DQ, 8 DI 24 V DC, sink/source, 8 DQ, relay 2 A

General information	
Product type designation	SM 1223, DI 8x24 V DC, DQ 8x relay
based on	<a href="#">6ES7223-1PH32-0XB0</a>
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	145 mA
Digital inputs	
• from load voltage L+ (without load), max.	4 mA/input 11 mA/relay
Output voltage	
Power supply to the transmitters	
• present	Yes
Power loss	
Power loss, typ.	5.5 W
Digital inputs	
Number of digital inputs	8
• in groups of	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	5 V DC at 1 mA
• for signal "1"	15 V DC at 2.5 mA
Input current	
• for signal "0", max. (permissible quiescent current)	1 mA
• for signal "1", min.	2.5 mA
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	

for standard inputs		
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four	
for interrupt inputs		
— parameterizable	Yes	
Cable length		
• shielded, max.	500 m	
• unshielded, max.	300 m	
<b>Digital outputs</b>		
Number of digital outputs	8	
• in groups of	2	
Short-circuit protection	No; to be provided externally	
Switching capacity of the outputs		
• with resistive load, max.	2 A	
• on lamp load, max.	30 W with DC, 200 W with AC	
Output voltage		
• Rated value (DC)	5 V DC to 30 V DC	
• Rated value (AC)	5 V AC to 250 V AC	
Output current		
• for signal "1" rated value	2 A	
• for signal "1" permissible range, max.	2 A	
Output delay with resistive load		
• "0" to "1", max.	10 ms	
• "1" to "0", max.	10 ms	
Total current of the outputs (per group)		
horizontal installation		
— up to 50 °C, max.	10 A; Current per mass	
Relay outputs		
• Number of relay outputs	8	
• Rated supply voltage of relay coil L+ (DC)	24 V	
• Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000	
Switching capacity of contacts		
— with inductive load, max.	2 A	
— on lamp load, max.	30 W with DC, 200 W with AC	
— with resistive load, max.	2 A	
Cable length		
• shielded, max.	500 m	
• unshielded, max.	150 m	
<b>Interrupts/diagnostics/status information</b>		
Alarms		
• Diagnostic alarm	Yes	
Diagnostics indication LED		
• for status of the inputs	Yes	
• for status of the outputs	Yes	
<b>Potential separation</b>		
Potential separation digital inputs		
• between the channels, in groups of	2	
Potential separation digital outputs		
• between the channels	Relays	
• between the channels, in groups of	2	
• between the channels and backplane bus	1 500 V AC for 1 minute	
<b>Permissible potential difference</b>		
between different circuits	750 V AC for 1 minute	
<b>Degree and class of protection</b>		
IP degree of protection	IP20	
<b>Standards, approvals, certificates</b>		
Ecological footprint		
• environmental product declaration	Yes	
Global warming potential		

— global warming potential, (total) [CO <sub>2</sub> eq]	123 kg
— global warming potential, (during production) [CO <sub>2</sub> eq]	12.1 kg
— global warming potential, (during operation) [CO <sub>2</sub> eq]	111 kg
— global warming potential, (after end of life cycle) [CO <sub>2</sub> eq]	-0.434 kg

#### Ambient conditions

Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C
• max.	70 °C; = Tmax; Tmax > +60 °C number of simultaneously activated outputs 4, inputs 4 (no adjacent points) for horizontal mounting position
• At cold restart, min.	-25 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m); above 2 000 m max. 132 V AC
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
• Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
• Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
• Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Connection method	
required front connector	Yes
Mechanics/material	

Enclosure material (front)	Yes																																											
• Plastic																																												
<b>Dimensions</b>																																												
Width	45 mm																																											
Height	100 mm																																											
Depth	75 mm																																											
<b>Weights</b>																																												
Weight, approx.	230 g																																											
<b>Classifications</b>																																												
	<table border="1"> <thead> <tr> <th></th> <th>Version</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>eClass</td> <td>14</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>12</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>9.1</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>9</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>8</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>7.1</td> <td>27-24-22-04</td> </tr> <tr> <td>eClass</td> <td>6</td> <td>27-24-22-04</td> </tr> <tr> <td>ETIM</td> <td>10</td> <td>EC001419</td> </tr> <tr> <td>ETIM</td> <td>9</td> <td>EC001419</td> </tr> <tr> <td>ETIM</td> <td>8</td> <td>EC001419</td> </tr> <tr> <td>ETIM</td> <td>7</td> <td>EC001419</td> </tr> <tr> <td>IDEA</td> <td>4</td> <td>3566</td> </tr> <tr> <td>UNSPSC</td> <td>15</td> <td>32-15-17-05</td> </tr> </tbody> </table>		Version	Classification	eClass	14	27-24-22-04	eClass	12	27-24-22-04	eClass	9.1	27-24-22-04	eClass	9	27-24-22-04	eClass	8	27-24-22-04	eClass	7.1	27-24-22-04	eClass	6	27-24-22-04	ETIM	10	EC001419	ETIM	9	EC001419	ETIM	8	EC001419	ETIM	7	EC001419	IDEA	4	3566	UNSPSC	15	32-15-17-05	
	Version	Classification																																										
eClass	14	27-24-22-04																																										
eClass	12	27-24-22-04																																										
eClass	9.1	27-24-22-04																																										
eClass	9	27-24-22-04																																										
eClass	8	27-24-22-04																																										
eClass	7.1	27-24-22-04																																										
eClass	6	27-24-22-04																																										
ETIM	10	EC001419																																										
ETIM	9	EC001419																																										
ETIM	8	EC001419																																										
ETIM	7	EC001419																																										
IDEA	4	3566																																										
UNSPSC	15	32-15-17-05																																										

<b>Approvals / Certificates</b>	
General Product Approval	EMV
<a href="#">Manufacturer Declaration</a>	
 EG-Konf.	
<a href="#">China RoHS</a>	
	<a href="#">KC</a>

EMV	Maritime application	Environment
		

last modified:

10/9/2024 