

Data sheet

6AG1243-5DX30-2XE0

product type designation



Figure similar

CM 1243-5

SIPLUS S7-1200 CM 1243-5 based on 6GK7243-5DX30-0XE0 with conformal coating, -25...+55 °C, communications module CM 1243-5, for connecting S7-1200 to PROFIBUS as DP master module

Technical Product Detail Page

<https://i.siemens.com/1P6AG1243-5DX30-2XE0>

transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS

9.6 kbit/s ... 12 Mbit/s

interfaces

number of interfaces / according to Industrial Ethernet

0

number of electrical connections

1

- at the 1st interface / according to PROFIBUS

1

- for power supply

type of electrical connection

9-pin Sub-D socket (RS485)

- at the 1st interface / according to PROFIBUS

3-pole terminal block

- for power supply

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / external

24 V

supply voltage / external / at DC / rated value

24 V

relative positive tolerance / at DC / at 24 V

20 %

relative negative tolerance / at DC / at 24 V

20 %

consumed current

0.1 A

- from external supply voltage / at DC / at 24 V / typical

power loss [W]

2.4 W

ambient conditions

ambient temperature

- for vertical installation / during operation

-25 ... +45 °C

- for horizontally arranged busbars / during operation

-25 ... +55 °C

- during storage

-40 ... +70 °C

- during transport

-40 ... +70 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity

- with condensation / according to IEC 60068-2-38 / maximum

100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation

chemical resistance / to commercially available cooling lubricants

Yes; incl. airborne diesel and oil droplets

resistance to biologically active substances

- conformity according to EN 60721-3-3

Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on

• conformity according to EN 60721-3-6	request Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances • conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
• conformity according to EN 60721-3-6	Yes
resistance to mechanically active substances • conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
• conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.134 kg
fastening method • 35 mm DIN-rail mounting	Yes
• S7-300 rail mounting	No
• wall mounting	Yes
product features, product functions, product components / general	
number of units • per CPU / maximum	3
performance data / PROFIBUS DP	
service / as DP master • DPV1	Yes
number of DP devices • on DP master / operable	32
data volume • of the address range of the inputs / as DP master / total • of the address range of the outputs / as DP master / total • of the address range of the inputs / per DP device • of the address range of the outputs / per DP device • of the address range of the diagnostic data / per DP device	512 byte 512 byte 244 byte 244 byte 240 byte
service / as DP device • DPV0 • DPV1	No No
performance data / S7 communication	
number of possible connections / for S7 communication • maximum • with PG connections / maximum • with PG/OP connections / maximum	8; max. 4 connections to other S7 stations 1 3
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode • without DP / maximum • with DP / maximum	8 8
performance data / telecontrol	
protocol / is supported • TCP/IP	No

product functions / management, configuration, engineering	
configuration software	STEP 7 Basic/Professional
• required	
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to website: Industrial communication	https://www.siemens.com/simatic-net
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAx-Download-Manager	https://siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>

Approvals / Certificates	EMV
General Product Approval	



[Manufacturer Declaration](#)



[China RoHS](#)



For use in hazardous locations	Maritime application
--------------------------------	----------------------

[CCC-Ex](#)



last modified:

10/28/2025