

SIPLUS S7-400 rack UR1 18-slot alu based on 6ES7400-1TA11-0AA0 with conformal coating, -25...+70 °C, central and distributed with 18 slots, 2 redundant PS can be plugged in



Figure similar

General information

Product type designation	UR1
based on	6ES7400-1TA11-0AA0

Hardware configuration

Rack	
• Communication bus	Yes
• P bus	Yes
Slots	
• Number of slots	18

Ambient conditions

Ambient temperature during operation	
• min.	-25 °C; = Tmin
• max.	70 °C; = Tmax
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)

Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN	Yes; Class 3 (excluding trichlorethylene)

60654-4

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04

Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)

Remark

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Conformal coating

- Coatings for printed circuit board assemblies acc. to EN 61086
- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Class 2 for high reliability

Yes; Type 1 protection

Yes; Discoloration of coating possible during service life

Yes; Conformal coating, Class A

Mechanics/material

rack profile material aluminum

Dimensions

Width 482.5 mm
Height 290 mm
Depth 27.5 mm

Weights

Weight, approx. 3 kg

Classifications

	Version	Classification
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03
eClass	9	27-24-22-03
eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

EMV



[Manufacturer Declaration](#)



[China RoHS](#)

[KC](#)



For use in hazardous locations

[CCC-Ex](#)



last modified:

6/18/2025