



Figure similar

SIMATIC ET 200SP HA, Carrier module in single carrier for holding one interface module of the ET 200SP HA incl. server module

| General information                      |        |                                    |                |
|------------------------------------------|--------|------------------------------------|----------------|
| Product type designation                 |        | IM carrier module, single          |                |
| Product function                         |        |                                    |                |
| ● I&M data                               |        | Yes; Asset data                    |                |
| Supply voltage                           |        |                                    |                |
| Rated value (DC)                         |        | 24 V                               |                |
| Hardware configuration                   |        |                                    |                |
| Slots                                    |        |                                    |                |
| ● Number of slots                        |        | 1                                  |                |
| Potential separation                     |        |                                    |                |
| between backplane bus and supply voltage |        | Yes                                |                |
| Isolation                                |        |                                    |                |
| Isolation tested with                    |        | 1 500 V DC/1 min, type test        |                |
| Ambient conditions                       |        |                                    |                |
| Ambient temperature during operation     |        |                                    |                |
| ● horizontal installation, min.          |        | -40 °C                             |                |
| ● horizontal installation, max.          |        | 70 °C                              |                |
| ● vertical installation, min.            |        | -40 °C                             |                |
| ● vertical installation, max.            |        | 60 °C                              |                |
| Dimensions                               |        |                                    |                |
| Width                                    |        | 100 mm                             |                |
| Height                                   |        | 204 mm                             |                |
| Depth                                    |        | 35 mm; measured without power plug |                |
| Weights                                  |        |                                    |                |
| Weight, approx.                          |        | 250 g                              |                |
| Classifications                          |        |                                    |                |
|                                          |        | Version                            | Classification |
|                                          | eClass | 14                                 | 27-24-26-07    |
|                                          | eClass | 12                                 | 27-24-26-07    |
|                                          | eClass | 9.1                                | 27-24-26-07    |
|                                          | eClass | 9                                  | 27-24-26-07    |
|                                          | eClass | 8                                  | 27-24-26-07    |
|                                          | eClass | 7.1                                | 27-24-26-07    |

|        |    |             |
|--------|----|-------------|
| eClass | 6  | 27-24-26-07 |
| ETIM   | 10 | EC001603    |
| ETIM   | 9  | EC001603    |
| ETIM   | 8  | EC001603    |
| ETIM   | 7  | EC001603    |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[China RoHS](#)



[KC](#)

General Product Approval

For use in hazardous locations



[Declaration of Con-  
formity](#)



For use in hazardous locations

Maritime application



[Miscellaneous](#)



Maritime application

Environment



[NK / Nippon Kaiji Ky-  
okai](#)



[CCS \(China Classifica-  
tion Society\)](#)

Siemens  
EcoTech



last modified: 10/23/2025