



SIMATIC ET 200SP HA, ET 200SP, BaseUnit type W0, for power module Ex-PM E, WxH: 50 mm x 117 mm



General information			
Product type designation		BU type W0	
Product function			
● I&M data		Yes; Asset data	
Current carrying capacity			
For P1 and P2 bus, max.		10 A	
Hardware configuration			
Formation of potential groups			
● support of potential groups		Yes	
● New potential group		Yes	
● Potential group continued from the left		No	
Slots			
● Number of slots		1	
Potential separation			
between backplane bus and supply voltage		Yes	
Isolation			
Isolation tested with		further information on insulation can be found in the "ET 200SP HA / ET 200SP modules for devices in hazardous areas" System Manual	
Ambient conditions			
Ambient temperature during operation			
● horizontal installation, min.		-40 °C	
● horizontal installation, max.		70 °C	
● vertical installation, min.		-40 °C	
● vertical installation, max.		60 °C	
Altitude during operation relating to sea level			
● Installation altitude above sea level, max.		2 000 m	
Dimensions			
Width		50 mm	
Height		117 mm	
Depth		19 mm	
Weights			
Weight, approx.		38 g	
Classifications			
		Version	Classification
eClass		14	27-24-26-07

eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval



[KC](#)



For use in hazardous locations

Maritime application



[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Environment



last modified:

3/26/2025 [↗](#)