

Data sheet

6DL9910-8EC

cable channel with lateral punching and top part for 650 mm cabinet width, color blue (RAL 5015), PVC, combustibility class V0 according to UL94, 60 x 80 mm (WxH), maximum number of EM/IM reduced to 12, incl. installation Ex device 6DL2804, can be ordered together with a new Ex device 6DL2804

General information			
Product type designation	cable duct 650 mm blue for 6DL2804		
Installation type/mounting			
Wall mounting/direct mounting	Yes; mounted in Ex device 6DL2804		
Standards, approvals, certificates			
Use in hazardous areas	<ul style="list-style-type: none">• ATEX marking• ATEX certificate• EAC Ex II 2 (1) G Ex eb db ib [ia Ga] IIC T4 Gb; II 2 (1) D Ex tb [ia Da] IIIC T130°C Db BVS 04 ATEX E 157 No		
Ambient conditions			
Ambient temperature during operation	<ul style="list-style-type: none">• min. -20 °C; down to -40 °C when using heater• max. 45 °C; typical, dependent on the power loss of the installed components		
Ambient temperature during storage/transportation	<ul style="list-style-type: none">• min. -40 °C• max. 70 °C		
Accessories			
Function description	cable duct 650 mm blue for 6DL2804		
belongs to product	6DL2804		
Weights			
Weight, approx.	0.5 kg		
Classifications			
		Version	Classification
		eClass	14
		eClass	12
		eClass	9.1
		eClass	9
		eClass	8
		eClass	7.1
		eClass	6
		ETIM	10
		ETIM	9
		ETIM	8
		ETIM	7

last modified:

11/24/2025 