



SIMATIC DP, electronic module ET 200SP, F-AI 4xI0(4)..20 mA HF fail-safe analog inputs up to PL e (ISO 13849) up to SIL 3 (IEC 61508)

General information	
Product type designation	F-AI 4xI 0(4)..20mA 2-/4-wire HF
Firmware version	
• FW update possible	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V15 with HSP 203
CiR - Configuration in RUN	
Reparameterization possible in RUN	No
Calibration possible in RUN	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
power supply according to NEC Class 2 required	No
Input current	
Current consumption (rated value)	0.38 A
Current consumption, max.	0.4 A
Encoder supply	
24 V encoder supply	
• 24 V	Yes; min. L+ (-1.5 V)
• Short-circuit protection	Yes
• Output current, max.	300 mA; total current of all encoders/channels
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
• Inputs	14 byte; S7-300/400F CPU, 13 byte
• Outputs	5 byte; S7-300/400F CPU, 4 byte
Hardware configuration	
Automatic encoding	Yes
• Electronic coding element type F	Yes
Analog inputs	
Number of analog inputs	4

• For current measurement	4
permissible input current for current input (destruction limit), max.	35 mA
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	125 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	125 Ω
Cable length	
• shielded, max.	1 000 m
Analog value generation for the inputs	
Measurement principle	Sigma Delta
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit
• Integration time, parameterizable	Yes
• Integration time (ms)	20 / 16,667
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
Smoothing of measured values	
• Number of smoothing levels	7
• parameterizable	Yes
• Step: None	Yes; 1x conversion cycle time
• Step: low	Yes; 2x / 4x conversion cycle time
• Step: Medium	Yes; 8x / 16x conversion cycle time
• Step: High	Yes; 32x / 64x conversion cycle time
Encoder	
Connection of signal encoders	
• for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	650 Ω
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.1 %
Temperature error (relative to input range), (+/-)	0.023 %/K
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.1 %
Operational error limit in overall temperature range	
• Current, relative to input range, (+/-)	2 %
Basic error limit (operational limit at 25 °C)	
• Current, relative to input range, (+/-)	0.1 %
Interference voltage suppression for $f = n \times (f1 \pm 1 \%)$, f1 = interference frequency	
• Series mode interference (peak value of interference < rated value of input range), min.	40 dB
• Common mode interference, min.	70 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Limit value alarm	No
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
• between the channels	No

• between the channels and backplane bus • between the channels and the power supply of the electronics	Yes																																										
	Yes																																										
Permissible potential difference																																											
between the inputs (UCM)	10 Vpp																																										
Isolation																																											
Isolation tested with	707 V DC (type test)																																										
Standards, approvals, certificates																																											
Ecological footprint																																											
• environmental product declaration	Yes																																										
Global warming potential																																											
— global warming potential, (total) [CO2 eq]	88.3 kg																																										
— global warming potential, (during production) [CO2 eq]	13.1 kg																																										
— global warming potential, (during operation) [CO2 eq]	76.6 kg																																										
— global warming potential, (after end of life cycle) [CO2 eq]	-1.37 kg																																										
Highest safety class achievable in safety mode																																											
• Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 61508	PLe Cat. 4 SIL 3																																										
Probability of failure (for service life of 20 years and repair time of 100 hours)																																											
— Low demand mode: PFDavg in accordance with SIL3	< 5.00E-05																																										
— High demand/continuous mode: PFH in accordance with SIL3	< 1.00E-09 1/h																																										
Ambient conditions																																											
Ambient temperature during operation																																											
• horizontal installation, min. • horizontal installation, max. • vertical installation, min. • vertical installation, max.	0 °C 60 °C 0 °C 50 °C																																										
Dimensions																																											
Width	15 mm																																										
Height	73 mm																																										
Depth	58 mm																																										
Weights																																											
Weight, approx.	48 g																																										
Classifications																																											
	<table><tr><td></td><td>Version</td><td>Classification</td></tr><tr><td>eClass</td><td>14</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>12</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>9</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>8</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-26-01</td></tr><tr><td>eClass</td><td>6</td><td>27-24-26-01</td></tr><tr><td>ETIM</td><td>10</td><td>EC001596</td></tr><tr><td>ETIM</td><td>9</td><td>EC001596</td></tr><tr><td>ETIM</td><td>8</td><td>EC001596</td></tr><tr><td>ETIM</td><td>7</td><td>EC001596</td></tr><tr><td>IDEA</td><td>4</td><td>3562</td></tr><tr><td>UNSPSC</td><td>15</td><td>32-15-17-05</td></tr></table>		Version	Classification	eClass	14	27-24-26-01	eClass	12	27-24-26-01	eClass	9.1	27-24-26-01	eClass	9	27-24-26-01	eClass	8	27-24-26-01	eClass	7.1	27-24-26-01	eClass	6	27-24-26-01	ETIM	10	EC001596	ETIM	9	EC001596	ETIM	8	EC001596	ETIM	7	EC001596	IDEA	4	3562	UNSPSC	15	32-15-17-05
	Version	Classification																																									
eClass	14	27-24-26-01																																									
eClass	12	27-24-26-01																																									
eClass	9.1	27-24-26-01																																									
eClass	9	27-24-26-01																																									
eClass	8	27-24-26-01																																									
eClass	7.1	27-24-26-01																																									
eClass	6	27-24-26-01																																									
ETIM	10	EC001596																																									
ETIM	9	EC001596																																									
ETIM	8	EC001596																																									
ETIM	7	EC001596																																									
IDEA	4	3562																																									
UNSPSC	15	32-15-17-05																																									
Approvals / Certificates																																											
General Product Approval																																											

[Miscellaneous](#)

[Manufacturer Declaration](#)



For use in hazardous locations



[CCC-Ex](#)

[FM](#)



[Miscellaneous](#)

For use in hazardous locations

Functional Safety

Maritime application

[Type Examination Certificate](#)

[TUEV](#)

[Type Examination Certificate](#)



Maritime application

other



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



[PROFIsafe](#)

last modified:

10/23/2025