



Figure similar

SIMATIC DP, Electronic module for ET 200 PRO 16 DI 24 V DC, Module diagnostics; incl. bus module, Connection module IO 6ES7194-4CB50-0AA0 order separately

General information	
Product function	
• Isochronous mode	No
Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; Against destruction; encoder power supply outputs applied with reversed polarity
Input current	
from supply voltage 1L+, max.	30 mA
from backplane bus 3.3 V DC, max.	20 mA
Encoder supply	
Number of outputs	8
Short-circuit protection	Yes; per module, electronic
Output current	
• up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Address space per module	
• Address space per module, max.	2 byte
Digital inputs	
Number of digital inputs	16
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	16
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms

— at "1" to "0", min.	0.7 ms
— at "1" to "0", max.	3 ms
Cable length	
• unshielded, max.	30 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Diagnostic information readable	Yes
• Short-circuit	Yes; Sensor supply to M; module by module
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes; Per channel
Potential separation	
between backplane bus and all other circuit components	Yes
Potential separation digital inputs	
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	140 g
Classifications	

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



EG-Konf.

[China RoHS](#)

[Miscellaneous](#)

[Manufacturer Declaration](#)



UL

General Product Approval	Maritime application
--------------------------	----------------------



[KC](#)



Maritime application

[NK / Nippon Kaiji Ky-
okai](#)



[CCS \(China Classifica-
tion Society\)](#)



last modified:

10/23/2025 