



SIMATIC ET 200AL, IO-Link, DQ 8x 24 V DC/2 A, 8x M12, Degree of protection IP67

General information	
Product type designation	IO-Link DQ 8x24VDC/2A
HW functional status	FS01
Firmware version	V1.0.x
Vendor identification (VendorID)	42
Device identifier (DeviceID)	229381
Engineering with	
• IODD file	Yes
Supply voltage	
Load voltage 1L+	
• Rated value (DC)	24 V; Supply from 1Us+ of the IO-Link master
• permissible range, lower limit (DC)	18 V
• permissible range, upper limit (DC)	30 V
• Reverse polarity protection	Yes; against destruction
Load voltage 2L+	
• Rated value (DC)	24 V; Supply via M12 connector L-coded
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes; against destruction; load increasing
Input current	
Current consumption (rated value)	12 mA; without load
from load voltage 2L+, max.	8 A; Maximum value
Power loss	
Power loss, typ.	3.6 W
Digital outputs	
Number of digital outputs	8
Current-sourcing	Yes
output type acc. to IEC 61131, type 2	Yes
Short-circuit protection	Yes; per channel, electronic
• Response threshold, typ.	2.8 A
Limitation of inductive shutdown voltage to	2L+ (-47 V)
Switching capacity of the outputs	
• on lamp load, max.	10 W
Load resistance range	
• lower limit	12 Ω
• upper limit	4 kΩ
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	

• for signal "1" rated value • for signal "1" permissible range, max. • for signal "0" residual current, max.	2 A (45 °C); 1 A (55 °C) 2 A; with inductive load to IEC 60947-5-1, DC-13 / AC-15 0.5 mA
Switching frequency	
• with resistive load, max. • with inductive load, max. • on lamp load, max.	100 Hz 0.1 Hz; 0.25 Hz at 25 °C 1 Hz
Total current of the outputs	
• Current per module, max.	8 A
Cable length	
• unshielded, max.	30 m
IO-Link	
IO-Link protocol 1.1	Yes
Transmission rate	38.4 kBd (COM2)
Cycle time, min.	2.1 ms
Size of process data, input per module	0 byte
Size of process data, output per module	1 byte
Supported IO-Link profiles	common profile
Cable length unshielded, max.	20 m
Connection of IO-Link devices	
• Port type A	Yes
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; channel by channel, parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnoses	
• Short-circuit	Yes; Outputs to ground; module by module
Diagnostics indication LED	
• Channel status display • for module diagnostics • For load voltage monitoring	Yes; green LED Yes; green/red LED Yes; green LED
Potential separation	
between the load voltages	Yes
Potential separation channels	
• between the channels • between the channels and the power supply of the electronics	No Yes
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	Yes; from FS01
Highest safety class achievable for safety-related tripping of standard modules	
• Performance level according to ISO 13849-1 • Category according to ISO 13849-1 • SIL acc. to IEC 62061 • remark on safety-oriented shutdown	PL d Cat. 3 SIL 2 https://support.industry.siemens.com/cs/de/en/view/39198632
Ambient conditions	
Ambient temperature during operation	
• min. • max.	-30 °C 55 °C
Connection method	
Design of electrical connection for the inputs and outputs	M12, 5-pin, A-coded
Type of electrical connection for IO-Link	M12, 5-pin, A-coded
Design of electrical connection for supply voltage	M12, 4-pin, L-coded
Dimensions	
Width	45 mm
Height	159 mm

Depth	45 mm
Weights	
Weight, approx.	168 g
Classifications	

	Version	Classification
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[Manufacturer Declaration](#)


EG-Konf.



[China RoHS](#)


UL

General Product Approval	Functional Safety	Maritime application
--------------------------	-------------------	----------------------


RCM

[TUEV](#)


ABS


BUREAU
VERITAS


DNV


LRS

Maritime application

[NK / Nippon Kaiji Kyokai](#)


RINA

[CCS \(China Classification Society\)](#)


KR
KOREAN REGISTER

last modified:

10/23/2025 