



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; direct connection, integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current	
from supply voltage 1L+, max.	16 A
from load voltage 2L+ (without load), max.	16 A
Accessories	
Function description	Terminal module direct: PROFIBUS DP and 24 V power; up to 6 x M20 cable glands
belongs to product	ET 200pro; IM154-1/2 DP
Dimensions	
Width	90 mm
Height	130 mm
Depth	100 mm
Weights	
Weight, approx.	292 g
Classifications	

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates
General Product Approval



[Manufacturer Declaration](#)



[China RoHS](#)

[Miscellaneous](#)



General Product Approval	Maritime application
--------------------------	----------------------



[KC](#)



Maritime application

[NK / Nippon Kaiji Ky-
okai](#)



[CCS \(China Classifica-
tion Society\)](#)



last modified:

4/7/2025 