

Data sheet

6ES7194-4AD00-0AA0



SIMATIC DP, connection module for PROFIBUS interface module ET 200 Pro; M12/7/8", 2x M12 and 2x 7/8", integrated address setter and terminating resistor for PROFIBUS DP; product phase-out planned – see SIOS 109989704

Input current			
from supply voltage 1L+, max.	8 A		
from load voltage 2L+ (without load), max.	8 A		
Accessories			
Function description	Terminal module M12 7/8": PROFIBUS DP and 24 V power; 2x M12 and 2x 7/8"		
belongs to product	ET 200pro; IM154-1/2 DP		
Dimensions			
Width	60 mm		
Height	130 mm		
Depth	60 mm		
Weights			
Weight, approx.	440 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----

Manufacturer Declara-
tion



China RoHS



For use in hazardous locations	Maritime application	Environment
--------------------------------	----------------------	-------------

[CCC-Ex](#)



last modified:

4/7/2025