

SIMATIC DP, Connection module for PROFINET interface module, ET 200 PRO, connection 2xRJ45, 2x push-pull plug-in connectors for PROFINET PN



Figure similar

Input current			
from supply voltage 1L+, max.	16 A; No current consumption, only infeed current, max. 16 A with derating		
from load voltage 2L+ (without load), max.	16 A; No current consumption, only infeed current, max. 16 A with derating		
Accessories			
Function description	IM PN, 2x RJ45, 2x PushPull interface module		
belongs to product	IM154-4 PN HF		
Dimensions			
Width	90 mm		
Height	130 mm		
Depth	51 mm		
Weights			
Weight, approx.	325 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-03
	eClass	12	27-24-26-03
	eClass	9.1	27-24-26-03
	eClass	9	27-24-26-03
	eClass	8	27-24-26-03
	eClass	7.1	27-24-26-03
	eClass	6	27-24-26-03
	ETIM	10	EC001598
	ETIM	9	EC001598
	ETIM	8	EC001598
	ETIM	7	EC001598
	IDEA	4	3560
	UNSPSC	15	32-15-17-04

Approvals / Certificates	
General Product Approval	



General Product Approval	Test Certificates	Maritime application	other
Miscellaneous  	Special Test Certificate 	Confirmation	

other	Railway		Dangerous goods	Environment	
	Special Test Certificate	Confirmation	Transport Information	Environmental Confirmations	

Environment
 Environmental Confirmations

last modified:

4/7/2025
