



SIMATIC S7-400, digital input SM 421, isolated 16 DI; UC 120/230V Inputs according to IEC1131-2 Type 2

Input current	
from backplane bus 5 V DC, max.	80 mA
Power loss	
Power loss, typ.	12 W
Digital inputs	
Number of digital inputs	16
Input characteristic according to IEC 61131	Type 2
Number of simultaneously controllable inputs	
• Number of simultaneously controllable inputs	16
Input voltage	
• Type of input voltage	AC/DC
• Rated value (UC)	230 V; 120/230 V UC (47 ... 63 Hz)
• for signal "0"	0 to 40 V AC/ -40 to +40 V DC
• for signal "1"	74 to 264 V AC; 80 to 264 V DC, -80 to -264 V
Input current	
• for signal "0", min.	0 mA; AC: 0 mA; DC: 0 mA
• for signal "0", max. (permissible quiescent current)	6 mA; AC: 6 mA; DC: 2 mA
• for signal "1", typ.	10 mA; at 120 V: 10 mA AC, 1.8 mA DC; at 230 V: 14 mA AC, 2 mA DC
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	20 ms; AC: 20 ms; DC: 15 ms
— at "1" to "0", max.	30 ms; AC: 30 ms; DC: 25 ms
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	5 mA; AC: 5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
• Status indicator digital input (green)	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	Yes
• between the channels, in groups of	4
• between the channels and backplane bus	Yes
Isolation	

Isolation tested with	1 500 V AC
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	650 g
Classifications	

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[China RoHS](#)



[KC](#)

General Product Ap- proval	EMV	For use in hazard- ous locations	Maritime application
-------------------------------	-----	-------------------------------------	----------------------



[FM](#)



Maritime application



[NK / Nippon Kaiji Ky-
okai](#)



Maritime application

[CCS \(China Classifica-
tion Society\)](#)

last modified: 6/7/2025