



Figure similar

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 14 bit, U/IResistor
8 AI, cycle time 0.416 ms

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V; Only required for supplying 2-wire transmitters
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	200 mA; for 8 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	1 000 mA
Power loss	
Power loss, typ.	4.9 W
Analog inputs	
Number of analog inputs	8
• For voltage/current measurement	8
• For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA; Permanent
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	Yes
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	10 MΩ
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	50 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 kΩ
Input ranges (rated values), resistors	
• 0 to 600 ohms	Yes

Cable length			
shielded, max.	200 m		
Analog value generation for the inputs			
Integration and conversion time/resolution per channel			
- Resolution with overrange (bit including sign), max. - Integration time, parameterizable - Basic conversion time (ms) - Interference voltage suppression for interference frequency f1 in Hz - Time constant of the input filter - Basic execution time of the module (all channels released)	14 bit; 14 / 14 / 14 Yes 52 µs none / 400 / 60 / 50 Hz 15 µs 0.42 ms		
Encoder			
Connection of signal encoders			
- for voltage measurement - for current measurement as 2-wire transducer - for current measurement as 4-wire transducer - for resistance measurement with two-wire connection - for resistance measurement with three-wire connection - for resistance measurement with four-wire connection	Yes; possible Yes Yes Yes; Line resistances are also measured Yes; Line resistances are also measured Yes		
Errors/accuracies			
Temperature error (relative to input range), (+/-)	0.03 %/K		
Operational error limit in overall temperature range			
- Voltage, relative to input range, (+/-) - Current, relative to input range, (+/-) - Resistance, relative to input range, (+/-)	0.7 %; ±0.7 % at ±1 V; ±0.9 % at ±10 V, 1 to 5 V 0.8 %; at ±20 mA, 4 to 20 mA 1 %		
Basic error limit (operational limit at 25 °C)			
- Voltage, relative to input range, (+/-) - Current, relative to input range, (+/-) - Resistance, relative to input range, (+/-)	0.6 %; 0.6 % at ±1 V; 0.75 % at ±10 V, 1 to 5 V 0.7 %; at ±20 mA, 4 to 20 mA 0.7 %; 0 to 600 ohms		
Interrupts/diagnostics/status information			
Diagnostics function	No		
Potential separation			
Potential separation analog inputs			
- Potential separation analog inputs - between the channels - between the channels and backplane bus - Between the channels and load voltage L+	Yes; internal/external No Yes Yes		
Isolation			
Isolation tested with	2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog part and L+/M; 2 120 V DC between analog part and local ground; 2 120 V DC between L+/M and local ground		
Dimensions			
Width	25 mm		
Height	290 mm		
Depth	210 mm		
Weights			
Weight, approx.	500 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420

ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[China RoHS](#)



[Metrological Approval](#)

General Product Approval EMV For use in hazardous locations

[KC](#)



For use in hazardous locations Maritime application

[FM](#)



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application



[CCS \(China Classification Society\)](#)

last modified: 6/7/2025