



SIMATIC S7-400, interface module Send IM 460-3 for distributed coupling up to 102 m, with C-bus

Figure similar

Input current			
from backplane bus 5 V DC, max.	1 550 mA		
Power loss			
Power loss, max.	7 750 mW		
Hardware configuration			
Cable length between first and last interface module, max.	102.25 m		
Connection method			
termination plug	6ES7461-3AA0-7AA0		
Dimensions			
Width	25 mm		
Height	290 mm		
Depth	280 mm		
Weights			
Weight, approx.	630 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			



[Miscellaneous](#)

[China RoHS](#)



[KC](#)

General Product Approval

EMV

For use in hazardous locations



[EM](#)

For use in hazardous locations

Maritime application



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

[CCS \(China Classification Society\)](#)

last modified:

6/7/2025