



SIMATIC S7-400, interface module receiver IM 461-0 for central coupling without for PS transfer, with C-bus

Figure similar

Input current			
from backplane bus 5 V DC, max.		290 mA	
Power loss			
Power loss, max.		1 450 mW	
Hardware configuration			
Cable length between first and last interface module, max.		5 m	
Connection method			
termination plug		6ES7461-0AA0-7AA1	
Dimensions			
Width		25 mm	
Height		290 mm	
Depth		280 mm	
Weights			
Weight, approx.		610 g	
Classifications			
		Version	Classification
	eClass	14	27-24-22-08
	eClass	12	27-24-22-08
	eClass	9.1	27-24-22-08
	eClass	9	27-24-22-08
	eClass	8	27-24-22-08
	eClass	7.1	27-24-22-08
	eClass	6	27-24-22-08
	ETIM	10	EC001423
	ETIM	9	EC001423
	ETIM	8	EC001423
	ETIM	7	EC001423
	IDEA	4	3564
	UNSPSC	15	32-15-17-05
Approvals / Certificates			
General Product Approval			

[Miscellaneous](#)



[China RoHS](#)



[KC](#)

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[EM](#)

For use in hazardous locations	Maritime application
--------------------------------	----------------------



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

[CCS \(China Classification Society\)](#)

last modified: 6/7/2025