



SIMATIC S7-1500, digital output module, DQ 8x24 V DC/5 A AUX, width 35 mm, 8 channels in groups of 4, 5 A / channel, 8 A / group, per group, two channels can be parallel-switched (2 x 8 A), 8 channels with pulse width modulation (PWM; max 12.5 kHz), front connector (screw terminal or push-in) to be ordered separately

General information	
Product type designation	DQ 8x24VDC/5A HS
HW functional status	from FS01
Firmware version	from V1.0.0
• FW update possible	Yes
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	Yes
• Prioritized startup	Yes
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	V18 with HSP 0434 / V20
• STEP 7 configurable/integrated from version	STEP 7 V5.7 or higher SP1 or higher
• PROFIBUS from GSD version/GSD revision	revision 3 / version 5.1
• PROFINET from GSD version/GSD revision	V 2.43 / -
Operating mode	
• DQ	Yes
• DQ with energy-saving function	Yes; Valve control
• PWM	Yes; max. 12.5 kHz
• Cam control (switching at comparison values)	No
• Oversampling	Yes
• MSO	Yes
• Integrated operating cycle counter	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 10 A per group
Input current	
Current consumption, max.	40 mA; 20 mA per group, no output is activated.
Output voltage	
Rated value (DC)	24 V
Power	
Power consumption from the backplane bus	0.55 W
Power loss	
Power loss, typ.	2.4 W
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	8
Current-sinking	No

Current-sourcing	Yes; Push-pull output
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
• Response threshold, typ.	10 A; 4 μ s response time
Open-circuit detection	No
Overload protection	Thermal overload protection
Limitation of inductive shutdown voltage to	M (-1 V)
Controlling a digital input	Yes
Digital output functions, parameterizable	
• Freely usable digital output	Yes
• PWM output	Yes
— Number, max.	8
— Cycle duration, parameterizable	Yes; 0.08 ... 100 ms
— ON period, min.	0 %
— ON period, max.	100 %
— Resolution of the duty cycle	0.1 %
— Minimum pulse duration	30 μ s
• Digital output with oversampling	Yes
— Number, max.	8
— Values per cycle, max.	16
Switching capacity of the outputs	
• with resistive load, max.	5 A
• with inductive load, max.	5 A
• on lamp load, max.	10 W
Load resistance range	
• lower limit	4.8 Ω
• upper limit	4 k Ω
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	5 A
• for signal "1" permissible range, max.	6 A; note derating data in the manual
• for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
• "0" to "1", typ.	3 μ s
• "1" to "0", typ.	3 μ s
Parallel switching of two outputs	
• for logic links	No
• for uprating	Yes; 8A for parallel connection of channel 0 and 1 / channel 4 and 5
• for redundant control of a load	No
Switching frequency	
• with resistive load, max.	12.5 kHz
• with inductive load, max.	12.5 kHz; According to IEC 60947-5-1, DC-13
• on lamp load, max.	12.5 kHz
Total current of the outputs	
• Current per channel, max.	5 A; see additional description in the manual
• Current per group, max.	8 A; see additional description in the manual
• Current per module, max.	16 A; see additional description in the manual
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	8 A
— up to 60 °C, max.	5 A
vertical installation	
— up to 40 °C, max.	5 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Isochronous mode	
Bus cycle time (TDP), min.	250 μ s

Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
• Diagnostic alarm	Yes
• Maintenance interrupt	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	No
• Short-circuit	Yes
• Group error	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels, in groups of	4
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	No
Security	
signed firmware update	Yes
data integrity	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	40 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	236 g
Classifications	

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419

ETIM	8	EC001419
ETIM	7	EC001419

Approvals / Certificates

General Product Approval

[Miscellaneous](#)

[KC](#)

[Manufacturer Declara-
tion](#)

[China RoHS](#)



EMV

For use in hazardous locations

[KC](#)



[CCC-Ex](#)

[FM](#)



[Type Examination Cer-
tificate](#)

For use in hazardous locations

Environment



[Miscellaneous](#)



last modified:

10/23/2025