

SIMATIC S7-1500 / ET 200MP; slot cover for the active backplane bus of S7-1500 for protection against ESD and for mechanical fixing on the S7-1500 mounting rail. unused slots must be provided with a slot cover! 5 units per packing unit

Degree and class of protection			
IP degree of protection	IP20		
Ambient conditions			
Ambient temperature during operation			
• min.	-30 °C		
• max.	60 °C		
• horizontal installation, min.	-30 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-30 °C		
• vertical installation, max.	40 °C		
Ambient temperature during storage/transportation			
• min.	-40 °C		
• max.	70 °C		
Air pressure acc. to IEC 60068-2-13			
• Operation, min.	795 hPa		
• Operation, max.	1 040 hPa		
• Storage/transport, min.	660 hPa		
• Storage/transport, max.	1 140 hPa		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m		
Relative humidity			
• Operation at 25 °C without condensation, max.	95 %		
Dimensions			
Width	25 mm		
Height	150 mm		
Depth	32 mm		
Classifications			
		Version	Classification
	eClass	14	27-24-22-92
	eClass	12	27-24-22-92
	eClass	9.1	27-24-22-92
	eClass	9	27-24-22-92
	eClass	8	27-24-92-90
	eClass	7.1	27-24-92-90
	eClass	6	27-24-92-90
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
	IDEA	4	3552
	UNSPSC	15	32-15-17-03

Approvals / Certificates	
General Product Approval	

[Manufacturer Declaration](#) [KC](#)

last modified:

8/2/2023 