

Data sheet

6ES7922-3BD00-0ANO

S7-300 FRONT CONN. 40 TO DB25F 3m	
***** spare part ***** cable with front connector for SIMATIC S7-300 40-pole (6ES7392-1AM00-0AA0) on 25-pole D-sub socket for ET200M; 0.50 mm ² length = 3 m	
target system	SIMATIC S7-300 PCS7 MTA
product type designation	MTA
product designation	Pre-assembled front connector MTA
electrical data	
operating voltage / at DC	
● rated value	24 V
● maximum	30 V
type of electrical connection	
● in the field	Connector strip
● on enclosure	Screw-type terminal
connection method	
wire length	3 m
number of channels	40
number of poles	40; of the front connector
standards, specifications, approvals	
certificate of suitability / cULus approval	No
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-30 ... +70 °C
mechanical data	
design of cable	Round cable
material / of the connection cable sheath	PVC
color / of cable sheath	Black
outer diameter / of cable sheath	10.6 mm; bundled single cores
conductor cross section / rated value	0.5 mm ²
net weight	0.921 kg
additional information	
internet link / to website: CAx-Download-Manager	https://siemens.com/cax
internet link / to website: Industry Online Support	https://support.industry.siemens.com
further information / internet links	
suitability for interaction	
● input card PLC	No
● PLC output card	Yes
suitability for use	
● digital signal transmission	Yes
● analog signal transmission	No
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
marketing text	The pre-assembled connection cable, with a cross-section of 0.50qmm and a length of 3m, with a 40-pole front connector for the SIMATIC ET200M in screw version and with a 25-pole D-Sub plug (socket) at the ends, is intended for connection to the PCS7 MTA system. This pre-assembled connection cable connects the signals of the SIMATIC I/Os with the MTA modules. This pre-assembled connection cable is part of the SIMATIC TOP connect cabling system for the fastest and safest system cabling. In addition to reduced wiring costs, sources of errors in cabling can be significantly reduced.
Classifications	
	Version
	Classification

eClass	14	27-24-22-20
eClass	12	27-24-22-20
eClass	9.1	27-24-22-20
eClass	9	27-24-22-20
eClass	8	27-24-92-05
eClass	7.1	27-24-92-05
eClass	6	27-24-92-05
ETIM	10	EC000237
ETIM	9	EC000237
ETIM	8	EC000237
ETIM	7	EC000237
IDEA	4	3553
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#) [Declaration of Conformity](#) [China RoHS](#)

last modified:

9/9/2025 