



S7-1500 FRONTCONN.. 20 CORES H05V-K 8.0M

Front connector for SIMATIC S7-1500 40 pole (6ES7592-1AM00-0XB0) with 20 single cores 0.5 mm<sup>2</sup> (1-20) Core type H05V-K Screw version L = 8.0 m

|                                                                                        |                                                                                                     |
|----------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Technical Product Detail Page                                                          | <a href="https://i.siemens.com/1P6ES7922-5BJ00-0AB0">https://i.siemens.com/1P6ES7922-5BJ00-0AB0</a> |
| target system                                                                          | SIMATIC S7-1500                                                                                     |
| suitability for use                                                                    | Digital I/O modules                                                                                 |
| product type designation                                                               | Flexible connection                                                                                 |
| product designation                                                                    | Front connector with single cores                                                                   |
| <b>electrical data</b>                                                                 |                                                                                                     |
| operating voltage / at DC                                                              |                                                                                                     |
| • rated value                                                                          | 24 V                                                                                                |
| • maximum                                                                              | 30 V                                                                                                |
| type of electrical connection                                                          |                                                                                                     |
| • in the field                                                                         | other                                                                                               |
| • on enclosure                                                                         | Screw-type terminal                                                                                 |
| continuous current / with simultaneous load on all cores / at DC / maximum permissible | 1.5 A                                                                                               |
| <b>connection method</b>                                                               |                                                                                                     |
| connector type                                                                         | <a href="#">6ES7592-1AM00-0XB0</a>                                                                  |
| wire length                                                                            | 8 m                                                                                                 |
| type of connecting terminal                                                            | Screw-type terminal                                                                                 |
| number of channels                                                                     | 20                                                                                                  |
| number of poles                                                                        | 40; of the front connector                                                                          |
| marking / of cores                                                                     | Number consecutively from 1 to 20 in white adapter contact = core number                            |
| <b>standards, specifications, approvals</b>                                            |                                                                                                     |
| certificate of suitability / cULus approval                                            | No                                                                                                  |
| <b>ambient conditions</b>                                                              |                                                                                                     |
| ambient temperature                                                                    |                                                                                                     |
| • during operation                                                                     | 0 ... 60 °C                                                                                         |
| • during storage                                                                       | -30 ... +70 °C                                                                                      |
| <b>mechanical data</b>                                                                 |                                                                                                     |
| design of cable                                                                        | H05V-K                                                                                              |
| material / of the connection cable sheath                                              | PVC                                                                                                 |
| color / of cable sheath                                                                | blue                                                                                                |
| RAL color number                                                                       | RAL 5010                                                                                            |
| outer diameter / of cable sheath                                                       | 2.2 mm; bundled single cores                                                                        |
| conductor cross section / rated value                                                  | 0.5 mm <sup>2</sup>                                                                                 |
| net weight                                                                             | 1.86 kg                                                                                             |
| <b>additional information</b>                                                          |                                                                                                     |
| internet link / to website: Industry Mall                                              | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| internet link / to web page: selection aid TIA Selection Tool                          | <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>                     |
| internet link / to web page: system cabling                                            | <a href="https://siemens.com/simatic-top-connect">https://siemens.com/simatic-top-connect</a>       |

|                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| internet link / to website: CAx-Download-Manager    | <a href="https://siemens.com/cax">https://siemens.com/cax</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| internet link / to website: Industry Online Support | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| further information / internet links                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| suitability for interaction                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| • input card PLC                                    | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| • PLC output card                                   | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| suitability for use                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| • digital signal transmission                       | Yes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| • analog signal transmission                        | No                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| other information                                   | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| marketing text                                      | The pre-assembled 40-pole front connector with 20 single wires of type H05V-K, conductor cross-section 0.5qmm, with a length of 8.0m in screw version is intended for connection to a digital I/O module of the SIMATIC S7-1500. This is plugged onto the module to be wired instead of the front connector. This allows the signals of the digital I/O module to be easily connected to the elements to be wired via the numbered individual wires. This front connector with single wires is part of the flexible connection of SIMATIC TOP connect for the fastest and safest system cabling. In addition to a 50% lower wiring effort, sources of errors in cabling can be significantly reduced. |

#### Classifications

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 14      | 27-24-22-20    |
| eClass | 12      | 27-24-22-20    |
| eClass | 9.1     | 27-24-22-20    |
| eClass | 9       | 27-24-22-20    |
| eClass | 8       | 27-24-92-05    |
| eClass | 7.1     | 27-24-92-05    |
| eClass | 6       | 27-24-92-05    |
| ETIM   | 10      | EC000237       |
| ETIM   | 9       | EC000237       |
| ETIM   | 8       | EC000237       |
| ETIM   | 7       | EC000237       |
| IDEA   | 4       | 3553           |
| UNSPSC | 15      | 32-15-17-03    |

#### Approvals / Certificates

##### General Product Approval

[Declaration of Con-  
formity](#)
[Manufacturer Declara-  
tion](#)
[China RoHS](#)

last modified: 11/14/2025 