

## Data sheet

6GT2002-0HD01

### product type designation



### RF170C communication module

RFID communication module RF170C for Installation in ET 200pro; Basic module for connection of 2 readers; with RS422 or RS232 without connection block.

Technical Product Detail Page

<https://i.siemens.com/1P6GT2002-0HD01>

### suitability for operation

ET 200pro distributed I/O together with RF200/300/1000, MV300/400/500, MOBY D/E//I U and RS-232 devices

### transfer rate

transfer rate / at the point-to-point connection / serial / maximum

115.2 kbit/s

### interfaces

design of the interface / for point-to-point connection

RS422/RS232 via connection block

number of readers / connectable

2

type of electrical connection

- of the backplane bus
- of the PROFIBUS interface
- of Industrial Ethernet interface
- for supply voltage

ET 200pro backplane bus  
(according to the head module)  
(according to the head module)  
ET 200pro backplane bus

design of the interface / to the reader / for communication

Internal plug to the connection block

### mechanical data

material

Thermoplastic (Valox 467, fiberglass reinforced)

color

IP Basic 714

tightening torque / of the screw for securing the equipment / maximum

1.5 N·m

### supply voltage, current consumption, power loss

supply voltage / at DC

- rated value
- 

24 V  
20 ... 30 V

consumed current

- at DC / at 24 V / without connected devices / typical
- from supply voltage 1L+ / maximum

0.13 A  
1 A

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-25 ... +55 °C  
-40 ... +70 °C  
-40 ... +70 °C

protection class IP

IP67

shock resistance

According to IEC 61131-2

shock acceleration

300 m/s<sup>2</sup>

vibrational acceleration

100 m/s<sup>2</sup>

### design, dimensions and weights

width

90 mm

height

130 mm

depth	35 mm	
net weight	0.27 kg	
fastening method	ET 200pro rack	
wire length / for RS 422 interface / maximum	1000 m	
<b>product features, product functions, product components / general</b>		
display version	(see connection block)	
product function / addressable transponder file handler	No	
protocol / is supported		
• S7 communication	Yes	
<b>product functions / management, configuration, engineering</b>		
type of parameterization	HSP	
type of programming	FB 45, FB 55, ID profile, library with functions, (FC 45/55 with restricted functionality)	
type of computer-switched communication	acyclic communication	
<b>standards, specifications, approvals</b>		
certificate of suitability	CE, FCC, cULus	
MTBF	77 a	
product function / is supported / identification link	No	
<b>standards, specifications, approvals / Environmental Product Declaration</b>		
Environmental Product Declaration	Yes	
global warming potential [CO2 eq]		
• total	101.43 kg	
• during manufacturing	16 kg	
• during operation	85.3 kg	
• after end of life	0.13 kg	
<b>accessories</b>		
accessories	Connection block for RF170C	
<b>further information / internet links</b>		
internet link	<ul style="list-style-type: none"> <li>to website: Selection guide for cables and connectors</li> <li>to web page: selection aid TIA Selection Tool</li> <li>to web page: identification and localization systems</li> <li>to web page: SiePortal</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	
	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a> <a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a> <a href="https://www.siemens.com/ident">https://www.siemens.com/ident</a> <a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a> <a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a> <a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>	
<b>security information</b>		
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a>. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert">https://www.siemens.com/cert</a>. (V4.7)</p>	
<b>Approvals / Certificates</b>		
<b>General Product Approval</b>		
<a href="#">Declaration of Con-formity</a>	    <a href="#">China RoHS</a>	



---

last modified:

11/11/2025 